

## **Gear Road Ranger 50**

*High Performance Transmission Fluid*

***Gear Road Ranger 50** has been developed from superior additive technology with high quality base oil. It has been formulated to meet the requirements of Road Ranger transmissions. This oil offers maximum transmission performance as required by modern power-shift transmissions, at the same time as providing superior gear wear protection and excellent thermal stability.*

### **Summary of Benefits**

- *Reduced maintenance costs*
- *Extended gear equipment life*
- *Prolonged oil service life*

### **Specifications:**

- *SAE 50*

**Product Code:** 4010

**Product Size:** 20L, 205L

Victoria  
40 Kimberly Road, Dandenong South, Victoria Australia 3175  
PO Box 4580, Dandenong South, Victoria Australia 3164  
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland  
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504  
PO Box 139, Deception Bay, Queensland, Australia, 4508  
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700





**PRECISION LUBRICANTS**

## Product Data Sheet

# Gear Road Ranger 50

### Typical Characteristics:

Specific Density at 15°C (kg/L)	0.888
Flash Point OCO (°C)	>225
Pour Point (°C)	-15
Viscosity Index	94
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	220
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	18.6

*\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

### Storage:

*All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.*

### Health, Safety and Environment

*A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.*

*The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au).*

Victoria  
40 Kimberly Road, Dandenong South, Victoria Australia 3175  
PO Box 4580, Dandenong South, Victoria Australia 3164  
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland  
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504  
PO Box 139, Deception Bay, Queensland, Australia, 4508  
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

