



# THE INNOVATIVE AUSTRALIAN

**NOW MEETS  
API: SP**

## **Senso Classic**

*High-Performance Engine Oil for Superior Wear and Protection*

**Senso Classic** is a high-performance lubricant blended with the finest quality mineral base oils and top-quality additive materials to provide the user with the best protection for the extensive range of vehicles requiring this specification. It gives superior engine cleanliness and wear protection.

### **Summary of Benefits:**

- Formulated using low phosphorous technology for the protection of catalytic converters in cars running on unleaded fuel.
- Superior performance over SL rated oils.
- Suitable for use in LPG and lightly loaded diesel engines both naturally aspirated and turbo- charged.
- Viscosity modifiers maintain fluidity during cold temperature start up to protect critical bearing surfaces through rapid circulation.

### **Specifications:**

- SAE Viscosity: 20W-50
- API: SP/CF
- ACEA: A2/B2-02
- Ford: M2C 153-E
- Mercedes: MB 229.1
- MIL-L-46152 E, 2104 E
- VW: 500.00, 501.00

**Product Code:** 1002

**Product Size:** 1L, 5L, 20L, 60L, 205L



14.02.19 V1

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**



**THE INNOVATIVE  
AUSTRALIAN**

## **Senso Classic**

*High-Performance Engine Oil for Superior Wear and Protection*

### **Typical Characteristics:**

Density at 15°C (kg/L)	0.896
Flash Point COC (°C)	225
Pour Point (°C)	-21
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	160
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	19.5
Viscosity Index	140
Sulphated Ash (%m)	<1.0

*\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

### **Storage:**

*All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.*

### **Health, Safety and Environment:**

*A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.*

The Safety Data Sheet is available at Royal Precision Lubricants website [www.royallubricants.com.au](http://www.royallubricants.com.au) or by email [info@royallubricants.com.au](mailto:info@royallubricants.com.au)

14.02.19 V1

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**